

Loctite® Power Grab Construction Adhesive

Features & Benefits:

- Very high initial tack
- Water clean up
- Low odor
- Repositionable
- Can be used on wood, metal, drywall, plaster, concrete, and brick



General Information:

Loctite® Power Grab® All Purpose Construction Adhesive is a premium quality, high strength adhesive which eliminates the use of screws and nails in many applications.

How to Use:

At least one surface must be porous. If non porous surface is glossy, sand to remove gloss and remove residue. Mounting surface must be clean, dry and free of foreign materials. Remove cap and cut the nozzle at desired angle and width. Apply adhesive with steady pressure to one of the surfaces to be bonded. For large areas, apply adhesive around the perimeter of the item, approximately 2 inches from the edge. Apply additional beads at 12 inch intervals. Open time is 25 minutes. Once the product is applied, you have 15 minutes to arrange or change the position of the substrate.

Clean up:

Power Grab® dries in approximately 24 hours depending on conditions. Wipe excess from skin, clothing and other surfaces before the product hardens. Do not use Power Grab® in permanently damp or wet areas. Protect product from freezing.

Use on These Products:

Soft Sound® Acoustic Panels, Soft Sound® Studio Foams, Soft Sound® Class A™ Studio Foams, Acoustic Foam Panels, Class A™ Acoustic Foam Panels, Convolved Foam Panels, Echo Absorber™, Quiet Board™

Coverage:

- 1/4 in. bead = approximately 31 lineal feet per cartridge

Product Availability:

- 1 - 10.1 oz. cartridge
- case of 12 - 10.1 oz. cartridges

Warnings and Limitations:

- Do not use Power Grab® in permanently damp or wet areas.
- Protect product from freezing.

ADDRESS

Soundproofcow
440 Ramsey Avenue
Chambersburg, PA 17201

PHONE

P: 1-866-9499-COW
F: (717) 261-1790

WEB

www.soundproofcow.com

