Beacon 9256



Beacon 9256

Specifications

Content	100% pre-consumer recycled polyester
Weight	9.7 ± 1.0 oz./lin. yd.
Width	54" min. useable
Repeat	.25" vertical .5" horizontal
Backing	none
Treatment	none

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Miscellaneous

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.



*Certification Marks owned by the Association for Contract Textiles, Inc.

Performance


Colorfastness to Light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
Colorfastness to Crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet

Breaking Strength (ASTM D5034)
225 lbf min. warp and 175 lbf min. fill
Seam Slippage (ASTM D4034)
70 lbf min. warp and 50 lbf min. fill

Pilling Resistance (ASTM D3511) Class 4 min.



Flammability
CA Technical Bulletin 117-2013 Section 1
NFPA 260/UFAC Fabric Classification - Class I
ASTM E84 Class I or A



Sustainability

100% recycled and recyclable
Terratex is a registered trademark of Duvaltex

