Dashing 1204

Dashing 1204

Specifications

Content	92% post-consumer recycled polyester 8% pre-consumer recycled polyester
Weight	10.9 ± 1.0 oz./lin. yd.
Width	66" min. useable
Repeat	2" vertical 2.4" horizontal

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Miscellaneous

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.



program. Additional testing of this U.L. recognized component fabric is not required on approved panels from participating manufacturers.

*Certification Marks owned by the Association for Contract Textiles, Inc.

ILAS.

Dapper Grey 1047



Polished Slate 1044



Classic Silver 1041



Refined Marble

1042

Genteel Beige 1043



Antique Sage 1045



Bespoke Tan 1046





PANEL

Performance

₩	Colorfastness to Light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
0	Colorfastness to Crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
×	Breaking Strength (ASTM D5034) 240 lbf warp and 190 lbf fill
*	Flammability (ASTM E84) Class I or A

Sustainability



100% recycled and recyclable terratex is a registered trademark of Duvaltex

