Groove 3497

Froth 020



Marigold 031



Guilford of Maine®

Rum 030



Winter 022




Smoke 024



Mocha 040

Spring 021



Graphite

Groove 3497

Specifications

Content	100% post-consumer recycled polyester
Weight	15.0 ± 1.0 oz./lin. yd.
Width	66" min. useable
Repeat	20" vertical 16.75" horizontal


Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Acoustical Performance

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

Acoustical Performance for Panel Applications (ISO 10534-2)



NRC of anechoic termination	1.00
NRC of fabric in front of anechoic termination	.90

Performance

*	Colorfastness to Light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours
U	Colorfastness to Crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet
×	Breaking Strength (ASTM D5034) 225 lbf min. warp and 180 lbf min. fill

Sustainability

Class I or Á



Flammability (ASTM E84)



Miscellaneous

Proudly woven in North America supporting our local communities.

Application testing of this product is recommended. Colors may vary between dye lots. This is a directional fabric.

Visit guilfordofmaine.com for samples.

