

**Bisque** 010



Maize 040



Greystone 020



**Sand** 041



Moss



**Mink** 050



Iron



Reeds 3078

## **Specifications**

Content

74% post-consumer recycled polyester 26% pre-consumer recycled polyester

Weight

 $11.6 \pm 1.0$  oz./lin. yd.

Width

66" min. useable

Repeat

12.5" vertical, 16.9" horizontal

## **Cleaning Code**

W-S

#### **Performance**



Colorfastness to Light (AATCC 16 Option 3)

Grade 4 min. at 40 hours



Colorfastness to Crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet



Breaking Strength (ASTM D5034) 250 lbf min. warp and 150 lbf min. fill

•



Flammability (ASTM E84)

Class I or A



American Micro Industries, Inc. Attn: SoundproofCow.com 440 Ramsey Avenue Chambersburg, PA 17201

sales@soundproofcow.com


Toll Free: 1-866-949-9COW

(1-866-949-9269) Local: 717-262-7206 Fax: 717-261-1790

### **Acoustical Performance**

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

# Acoustical Performance for Panel Applications (ISO 10534-2)



NRC of anechoic termination

NRC of fabric in front of anechoic termination .95

### **Miscellaneous**

Colors may vary slightly between dye lots. This is a directional fabric. Application testing of this product is recommended.

# Guilford of Maine®

Visit guilfordofmaine.com for complete specs and samples.



Terratex is a registered trademark of True Textiles, Inc. and designates fabrics that are made from 100% recycled or compostable material using increasingly sustainable manufacturing practices to produce a high quality product that is recyclable at the end of its useful life. (terratex.com)



 ${\rm CO_2}$  emissions from 100% of the electricity used by the manufacturer to produce this product have been measured and offset in accordance with The CarbonNeutral Protocol.



This pattern is included in the underwriters laboratory panel fabric recognition program. Additional testing of this U.L. recognized component fabric is not required on approved panels from participating manufacturers.

\*ACT® registered certification marks.