

# Resilmount™ Betafix Adjustable Furring Channel Clip

## Features & Benefits

- Eliminates time consuming shimming
- Four adjustable locations
- Pre-punched with fixing holes
- 0-3/4" adjustment with 3/16" increments
- Adaptable to most applications
- Manufactured under ISO9001 Quality Control System



## General Information

Resilmount™ Betafix Adjustable Furring Channel Clips are used to provide adjustment for masonry walls and ceilings. This eliminates the need for packers and extra fasteners and provides for a faster, more accurate installation. Once the clip is securely fastened onto the wall or ceiling, the furring channel can be snapped in without the need of any extra fasteners.

## Specifications

- Coverage: 48" maximum spacing on furring channel, spacing between furring channels should not exceed 24"
- Load Capacity: 55 lbs.
- Use with 25 gauge furring channel
- Fasten with #8 screw or masonry sleeve

## Applications

Professional and Home Theaters · Professional and Home Recording Studios · Offices · Multi and Single Family Dwellings · Restaurants · Band Practice Rooms · Broadcast Rooms · Equipment Rooms · Workshops · Classrooms

### ADDRESS

Soundproofcow  
440 Ramsey Avenue  
Chambersburg, PA 17201

### PHONE

P: 1-866-9499-COW  
F: (717) 261-1790

### WEB

[www.soundproofcow.com](http://www.soundproofcow.com)

