

# PL<sup>®</sup> Premium Construction Adhesive

## Features & Benefits:

- 3 times stronger than ordinary adhesives
- Water and weatherproof
- Repositionable
- Can be used on wood, metal, OSB, drywall, concrete, masonry and bricks



## General Information:

PL<sup>®</sup> Premium Construction Adhesive is a polyurethane adhesive that provides superior results and is safer to use than ordinary adhesives. PL<sup>®</sup> Premium generates three times the power of traditional construction adhesives, may be used inside or outside and will last as long as the surfaces it joins together.

## How to Use:

To ensure positive adhesion, make sure the surfaces to be joined are clean and free of dirt and foreign material. Cut the smallest opening possible in spout (just large enough so adhesive can flow easily when gunned). Because of PL<sup>®</sup> Premium's unusual strength, much less adhesive is needed compared to traditional construction adhesives. Place cartridge in caulking gun and puncture seal inside spout with nail. Apply by forcing adhesive onto surfaces. When working on rough surfaces, use enough adhesive to fill gaps. PL<sup>®</sup> Premium will bridge up to 3/8". Use mechanical fasteners to hold the surface in place until the adhesive fully cures. Drying time may vary, depending on the humidity and porosity of the materials bonded together. PL Premium's reactive nature allows the formation of high strength bonds quickly. Many applications will develop full strength in less than 24 hours. Material may be repositioned up to 30 minutes without losing adhesive strength.

## Clean up:

It is highly recommended that gloves be worn. Once cured PL Premium is difficult to remove from skin and clothing. Immediately after use, clean up spills with mineral spirits following solvent manufacturer's precautions.

## Use on These Products:

Quiet Barrier<sup>®</sup>, Quiet Barrier<sup>®</sup> Foam Composites, Quiet Barrier<sup>®</sup> Specialty Composites, Soft Sound<sup>®</sup> Acoustic Panels, Soft Sound<sup>®</sup> Studio Foams, Soft Sound<sup>®</sup> Class A<sup>™</sup> Studio Foams, Acoustic Foam Panels, Class A<sup>™</sup> Acoustic Foam Panels, Convolved Foam Panels, Echo Absorber<sup>™</sup>, Quiet Board<sup>™</sup>

## Coverage:

- 1/4 in. bead = approximately 32 lineal feet per cartridge

## Product Availability:

- 1 - 10.2 oz. cartridge
- case of 12 - 10.2 oz. cartridges

## Warnings and Limitations:

- Temperatures below 40° F may cause slower cure rate.

### ADDRESS

Soundproofcow  
440 Ramsey Avenue  
Chambersburg, PA 17201

### PHONE

P: 1-866-9499-COW  
F: (717) 261-1790

### WEB

[www.soundproofcow.com](http://www.soundproofcow.com)

