

Acoustical Sound Sealant

Features & Benefits:

- UL tested and classified
- Non-flammable formulation
- Easy application and clean up
- Will not harden, crack or separate
- Non-staining and non-migrating
- High degree of adhesive and cohesive strength



General Information:

OSI® Pro-Series® SC-175™ Acoustical Sound Sealant is a water based sealant designed to reduce sound transmissions in walls and partition systems. Primary function is to achieve and maintain the specific STC (Sound Transmission Class) value of the system design. VOC compliant. Cleans up with soap and water. Cure time is 2 - 7 days depending on conditions.

Best Uses:

OSI® Pro-Series® SC-175™ Acoustical Sound Sealant was developed primarily for commercial construction utilizing light weight cavity walls and floor systems. The sealant is used for exposed and unexposed applications at perimeter joints, floor and ceiling runners (either wood or metal), cut-outs in gypsum board, veneer plaster systems and other areas where a sound rated assembly is required.

Coverage:

- 1/4 in. bead = approximately 86 lineal feet per cartridge
- 3/8 in. bead = approximately 38 lineal feet per cartridge

Product Availability:

- 1 - 28 oz. cartridge
- case of 12 - 28 oz. cartridges

ADDRESS

Soundproofcow
440 Ramsey Avenue
Chambersburg, PA 17201

PHONE

P: 1-866-9499-COW
F: (717) 261-1790

WEB

www.soundproofcow.com

