

Clearco 444 Foam Spray Adhesive

Features & Benefits:

- Engineered for foam applications
- Web spray pattern for clean application
- Does not contain Chlorinated Solvents
- Can be used on wood, metal, OSB, drywall, concrete, masonry and bricks



General Information:

Clearco 444 Spray Adhesive is a high performance acoustic foam spray adhesive. The bond is strong and long lasting. It bonds to a large variety of surfaces and is easy to apply. Clearco 444 Spray Adhesive has a “lace” spray pattern that is easy to control so over spray and clean-up is minimal. This adhesive is best for protected, indoor applications. Always use proper ventilation when applying this product.

How to Use:

To ensure positive adhesion, make sure the surfaces to be joined are clean and free of dirt and foreign material. Test the spray pattern on a piece of scrap paper or cardboard to get the feel how the spray applicator works. Then spray the product surface and the mounting surface. Both surfaces must be applied with the adhesive spray for a permanent bond. Allow at least five minutes for the adhesive to “tack” before bonding the product to the mounting surface. Always allow proper ventilation when using this type of product. Drying time may vary, depending on the humidity and porosity of the materials bonded together. Take care in placing the material the first time. Adhesion is immediate and there is no repositioning once the bonding surface and product are in contact.

Clean up:

It is highly recommended that gloves be worn. Once cured, Clearco 444 Spray Adhesive is difficult to remove from skin and clothing. The best way to limit clean-up is to be careful while applying this product.

Use on These Products:

Quiet Barrier® Foam Composites, Quiet Barrier® Specialty Composites, Class A Studio Foam Panels, Soft Sound® Studio Foams, Class A Acoustic Foam Panels, Acoustic Foam Panels, Convuluted Acoustic Foam Panels

Coverage:

- 48 sq.ft. per container when both mounting surface and product are sprayed

Product Availability:

- 1 - 12 oz. container
- case of 12 - 12 oz. containers

Warnings and Limitations:

- Temperatures below 55° F may cause slower cure rate.
- Harmful or fatal if swallowed
- Vapor is harmful
- Keep out of reach of children
- Extremely flammable
- Contents under pressure
- Eye irritant

ADDRESS

Soundproofcow
440 Ramsey Avenue
Chambersburg, PA 17201

PHONE

P: 1-866-9499-COW
F: (717) 261-1790

WEB

www.soundproofcow.com

