



## Impact Barrier® QT Technical Specifications

### Material:

Made from 92% recycled SBR (Styrene-Butadiene Rubber) tire rubber. QT is a flat, resilient underlayment that is used directly under a variety of floor finishes, yielding exceptional results for impact sound insulation and protecting ceramic tile, porcelain, and stone from substrate cracks.

**Patent No.** US RE 41, 945

### Sheet Dimension:

QT rolled rubber underlayment will have an over thickness of \_\_\_\_\_ (specify 1/8" [2 mm] standard in 4' by 75' [1.2 m by 22.9 m] roll size or 1/4" [5 mm] standard in 4' by 30' [1.2 m by 9.1 m] roll size or 3/8" [10 mm] standard in 4' by 15' [1.2 m by 4.6 m] roll size).

### Sheet Weight:

0.30 lb/ft<sup>2</sup> [1.4 kg/m<sup>2</sup>], 0.74 lb/ft<sup>2</sup> [3.6 kg/m<sup>2</sup>], 1.5 lb/ft<sup>2</sup> [7.2 kg/m<sup>2</sup>]

### Sheet Standard Tolerances:

Roll width: +3/4" - 0", Roll Length: +1% - 0", Thickness: ± 0.3 mm

### Impact Insulation Class Laboratory (ASTM E492):

Specified floor-ceiling assembly must be tested in a NVLAP certified laboratory and comply with ASTM standards.

### Impact Insulation Class Field (ASTM E1007):

Floor-ceiling assembly must meet requirement as stated by building code and/or acoustical consultant.

### ASTM E2179:

Shall be LAB tested over a 6" concrete slab with tile, no ceiling assembly, with an IIC rating of 50 or greater.

Shall be IIC-ES certified

Shall be UL listed

**VOC Washington State IAQ Test (ASTM D5116):** pass



### ADDRESS

Soundproofcow  
440 Ramsey Avenue  
Chambersburg, PA 17201

### Phone

P: 1-866-949-9COW  
F: (717) 261-1790

### WEB

[www.soundproofcow.com](http://www.soundproofcow.com)