

Quiet Barrier[®] Tape

Light Duty Mass Load Vinyl Sound Barrier Tape with Pressure Sensitive Adhesive backing

Features & Benefits:

- Improved Soundproofing Performance Your wall or ceiling assembly is only soundproofed
 if the seams of our Quiet Barrier® are bonded and sealed. Quiet Barrier® Tape will effectively bond and seal sheets of our flexible soundproofing materials. The better the seams
 are sealed, the better the overall performance of our sound blocking materials.
- Ease of installation Quiet Barrier® Tape has a Pressure Sensitive Adhesive (PSA) backing for an easy "peel and place' application.
- Low Profile The total thickness of Quiet Barrier[®] Tape is 1/16 inch and will easily fit in locations where space is limited. It will not cause wall or ceiling finishing materials, like drywall or paneling, to distort or bow.



General Information:

Quiet Barrier® Tape effectively seals the seams between sheets of Quiet Barrier® or Quiet Barrier® Foam Composites. Quiet Barrier® Tape has the same noise blocking and sound damping qualities as our Quiet Barrier® Soundproofing Materials. In essence, it is ½ lbs Quiet Barrier® that is 1/16 inch thick, 3 inches wide and 96 inches long. Quiet Barrier® Tape has a Pressure Sensitive Adhesive backing for an easy "peal and place" application. Quiet Barrier® Tape has excellent resistance to chemicals and petroleum products.

Use on These Products:

Quiet Barrier®, Quiet Barrier® Foam Composites

Coverage:

8 linear feet per roll of tape

Product Availability:

- 1/16 in. thick x 3 in. x 96 in. roll
- · Custom dimensions available upon request.

ADDRESS

SoundproofCow 440 Ramsey Avenue Chambersburg, PA 17201

PHONE

P: 1-866-949-9COW F: (717) 261-1790

WEB

www.soundproofcow.com

