

Quiet Barrier[®] Tape

Features & Benefits:

- **Improved Soundproofing Performance** - Your wall or ceiling assembly is only soundproofed if the seams of our Quiet Barrier[®] are bonded and sealed. Quiet Barrier[®] Tape will effectively bond and seal sheets of our flexible soundproofing materials. The better the seams are sealed, the better the overall performance of our sound blocking materials.
- **Ease of installation** - Quiet Barrier[®] Tape has a Pressure Sensitive Adhesive (PSA) backing for an easy “peel and place” application.
- **Low Profile** - The total thickness of Quiet Barrier[®] Tape is 1/16 inch and will easily fit in locations where space is limited. It will not cause wall or ceiling finishing materials, like drywall or paneling, to distort or bow.



General Information:

Quiet Barrier[®] Tape effectively seals the seams between sheets of Quiet Barrier[®] or Quiet Barrier[®] Foam Composites. Quiet Barrier[®] Tape has the same noise blocking and sound damping qualities as our Quiet Barrier[®] Soundproofing Materials. In essence, it is ½ lbs Quiet Barrier[®] that is 1/16 inch thick, 3 inches wide and 96 inches long. Quiet Barrier[®] Tape has a Pressure Sensitive Adhesive backing for an easy “peel and place” application. Quiet Barrier[®] Tape has excellent resistance to chemicals and petroleum products.

Use on These Products:

Quiet Barrier[®], Quiet Barrier[®] Foam Composites

Coverage:

- 8 linear feet per roll of tape

Product Availability:

- 1/16 in. thick x 3 in. x 96 in. roll
- Custom dimensions available upon request.

ADDRESS

Soundproofcow
440 Ramsey Avenue
Chambersburg, PA 17201

PHONE

P: 1-866-9499-COW
F: (717) 261-1790

WEB

www.soundproofcow.com

