

Reinforced Aluminum Tape

Features & Benefits:

- Very Durable Reinforced Aluminum Seam Tape is Tri-directionally reinforced with 2 x 3 squares per inch fiberglass scrim.
- Hot and Cold Tolerant The cold weather acrylic adhesive performs well over a wide temperature range. The continuous temperature range is -35°F to 260°F.
- Ease of installation Reinforced Aluminum Seam Tape has an acrylic adhesive backing for an easy "peel and place' application. This product is hand tearable or if a more refined finished appearance is desired, it can be cut with scissors.
- Flammability Reinforced Aluminum Seam Tape is UL723 Listed.



General Information:

Reinforced Aluminum Seam Tape is a 5 mil tape specially designed to seal seams between our aluminum or Polyester Film faced acoustic products to achieve maximum results and attain a nice finished appearance. Reinforced Aluminum Seam Tape may be used to repair rips, tears and imperfections that may have occurred while installing our foil or Polyester Film faced soundproofing products. Reinforced Aluminum Seam Tape excels in demanding temperature and humidity applications and provides superior performance and durabil-ity over a wide range of environmental conditions. Reinforced Aluminum Seam Tape is heat and light reflective. This product is UL Classified and has been tested and approved to inhibit mold. The tape is 3 inches wide and 50 yards long. The adhesive is an all weather acrylic and has a continuous temperature range from -35°F to 260°F.

Use on These Products:

Quiet Barrier® Specialty Foam Composite, Any of our Acoustic Foam Panels or Class A™ Acoustic Foam Panels with a reinforced alumi-num or reinforced Polyester Film facing.

Product Availability and Coverage:

• 5.0 mil thick x 3 inch x 50 yard roll (covers 150 linear ft.)

Special Order:

- 5.0 mil thick x 4 inch x 50 yard roll
- 5.0 mil thick x 5 inch x 50 yard roll
- 5.0 mil thick x 6 inch x 50 yard roll

