Off the Grid 1233



Specifications

Content	49% pre-consumer recycled polyester 38% post-consumer recycled polyester 13% polyester	
Weight	10.0 ± 1.0 oz./lin. yd	
Width	66" min. useable	
Repeat	none	
Treatment	polyester binder	

Off the Grid 1233

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup. May also be disinfected with hydrogen peroxide, alcohol, and quaternary ammonium (quat) based cleaners.

Miscellaneous

- · Application testing of this product is recommended.
- · Colors may vary between dye lots.
- · This is a directional fabric.

Proudly woven in North America supporting our local communities.

Sustainability



Performance

*	Colorfastness to light (AATCC 16.3 Option 3) Grade 4 min. at 40 hours	
U	Colorfastness to crocking (AATCC 8) Grade 4 min. dry & Grade 3 min. wet	
太	Breaking Strength (ASTM D5034) 185 lbf warp and 165 lbf fill	




Flammability

Acoustical Performance

Our acoustic fabrics are all acoustically transparent. This represents the amount of sound that passes through the fabric.

Acoustic Transparency:	100%

For more detailed results, please consult our website.



*Certification Marks owned by the Association for Contract Textiles, Inc.

